

Raccordi tipo RCX MG

Fitting type RCX MG



disponibile nei colori:
colors available:



Settori di Impiego / Areas of application



Caratteristiche / Characteristics:

Raccordo maschio girevole dritto realizzato in PVC autoestinguente. Massima facilità di montaggio disponibile nelle versioni passo GAS, PG e ISO METRICO. Questi raccordi sono adatti per tutte le guaine spiraleate già esistenti in commercio. Grado di protezione IP65

Swivel male straight fitting manufactured in self extinguishing PVC. These fittings are very easy to assemble and are suited for every flexible PVC spiral conduit already present on the market. Protection class IP65

Raccordo maschio girevole dritto per guaine spiraleate / Swivel male straight fitting

Codice Code	Filetto Thread GAS ISO 228	Codice Code	Filetto Thread PG DIN 40430	Codice Code	Filetto Thread METRICO ISO R68	Tubo Conduit ø int.	Confezione Package
						mm	N° pz.
80000	1/4"	-	-	-	-	8,0	25
80001	1/4"	80031	9	80060	⊗ M16*1,5	10,0	25
80002	3/8"	80032	11	80061	⊗ M16*1,5	12,0	25
-	-	80033	13,5	-	-	12,0	25
80003	1/2"	80034	13,5	-	-	14,0	25
80004	1/2"	80035	11	80062	⊗ M20*1,5	16,0	25
-	-	80036	13,5	-	-	16,0	25
-	-	80037	16	-	-	16,0	25
80005	3/4"	80038	21	80063	⊗ M25*1,5	20,0	25
80006	3/4"	80039	21	-	-	22,0	25
80007	1"	80040	29	80065	⊗ M32*1,5	25,0	10
80008	1"	80041	29	-	-	28,0	10
80009	1" 1/4	80042	36	80066	⊗ M40*1,5	32,0	10
80010	1" 1/4	80043	36	-	-	35,0	10
80011	1" 1/2	-	-	80067	⊗ M50*1,5	40,0	10
80012	2"	-	-	80068	⊗ M63*1,5	50,0	10

Aggiungere al codice: N=Nero
Add to code: N= Black